

# SMART PRODUCTS

## Series oxygen Generator ◀



SMART series PSA O<sub>2</sub> generators are developed for small health care institutions, especially for low flow, continuous use of medical O<sub>2</sub> demand. A stand alone system with highly compact , plug and run design and wide applicabilities, SMART series PSA O<sub>2</sub> generators are excellent in performance, reliability and convenience.

### Product features:

- **Compact:** Built-in high quality oil-injected screw compressor, dryer and Multi-stage filters.
- **Reliable and stable:** 7\*24hrs design, no performance degradation.
- **Low Noise:** Sturdy and noise reduction industrial cabinet.
- **Convenient and easy installation:** Plug in and run design. Heavy duty casters, allowing easy and time saving installation.
- **High Efficiency:** Low power consumption.
- **Reliable:** Time-proven PSA technology.
- **Wide applicabilities:** Many model and function options.

### CAN GAS SYSTEMS COMPANY LIMITED

Add: B514~516, GID International Center, 27 Nanbinhe Road, Xicheng District, Beijing, China, 100055.

Phone: +86 400-116-9800

Fax: +86 10 63338230

E-mail: sales@can-gas.com

Website: www.can-gas.net

**Time-proven CanGas® medical gas system and engineering solutions, unique multiple protection and redundancy backup design, ensure worry-free supply of medical gas at site.**

**SMART Oxygen Generator Package Specification:**

(For different power supply, please consult with CAN GAS sales for more details.)

Model	SMART CAP-O-3/2C	SMART CAP-O-3/3C	SMART CAP-O-5/5C
O <sub>2</sub> Purity	93%±3%		
O <sub>2</sub> Flow Rate	2.0~2.5Nm <sup>3</sup> /h	3~3.5Nm <sup>3</sup> /h	5Nm <sup>3</sup> /h
O <sub>2</sub> Delivery Pressure	0.4MPa		
Installed Power	5.0kW, 380V/50Hz 3PH	6.5kW, 380V/50Hz 3PH	8.5kW,380V/50Hz 3PH
Dimension	1600*900*1600(mm)		
Weight	650Kg		750Kg
Jobsite Altitude	≤2000m		



**CAN GAS SYSTEMS COMPANY LIMITED**

Add: B514~516, GID International Center, 27 Nanbinhe Road, Xicheng District, Beijing, China, 100055.

Phone: +86 400-116-9800

Fax: +86 10 63338230

E-mail: sales@can-gas.com

Website: www.can-gas.net



**Product features:**

- **Credibility:** All SMART O<sub>2</sub> generators modulars are manufactured and tested in CAN GAS ISO9001, ISO45001/14001 certificated factory and strictly quality controlled in accordance to ISO13485, YY, GB related medical equipment standards.
- **Reliable and stable:** 7\*24hrs design, time-proven CanGas PSA technology.
- **Low Noise:** Sturdy and noise reduction industrial cabinet.
- **Convenient and easy installation:** Plug in and run design. Heavy duty casters, allowing easy and time saving installation.
- **High Efficiency:** Low power consumption.
- **Wide applicabilities:** Many model and function options.

Model	CAP-O-3/2C	CAP-O-3/3C	CAP-O-5/5C
O <sub>2</sub> Purity	93%±3%		
O <sub>2</sub> Flow Rate	2.0~2.5Nm <sup>3</sup> /h	3.0~3.5Nm <sup>3</sup> /h	5.0Nm <sup>3</sup> /h
O <sub>2</sub> Outlet Size	G1/2"		
O <sub>2</sub> Delivery Pressure	0.4MPa		
Installed Power	0.3kW, 220V/50Hz/60Hz 1PH		
Dimension	450*900*1600(mm)		
Weight	280Kg	380Kg	

**CAN GAS SYSTEMS COMPANY LIMITED**

Add: B514~516, GID International Center, 27 Nanbinhe Road, Xicheng District, Beijing, China, 100055.

Phone: +86 400-116-9800

Fax: +86 10 63338230

E-mail: sales@can-gas.com

Website: www.can-gas.net

# SMART CAWG Desiccant Dryer

## ► Clean Dry Compressed Air System



The SMART CAWG can work with SMART air unit to optimize air drying system, designed to make SMART O<sub>2</sub> generator package delivering consistent high performance over an extended period, to ensure a long operational life.

### Product features:

- **Compact:** Standard modular design, compact and small footprint.
- **Reliable and stable:** Time-proven CanGas technology, high performance.
- **Economic:** Combined drying design, low air consumption.
- **Auto-control:** PLC control, optional CANBUS touch screen control, offering real-time information.
- **Convenient:** One unit, duplex and multiple units can be deployed easily, heavy duty casters, allowing easy and time saving installation.



Model	CAWG - 16C	CAWG - 24C
Capacity	1.6m <sup>3</sup> /min	2.4m <sup>3</sup> /min
Dew Point	- 20°C ~ - 40°C	
working pressure	0.4MPa~1.0MPa	
working temperature	2°C~50°C	
Maximum environment temperature	55°C	
Installed power	0.3kW, 220V 1PH	
Size	450*900*1600(mm)	
Connection size	G1/2"	
Weight	200kg	280kg

### CAN GAS SYSTEMS COMPANY LIMITED

Add: B514~516, GID International Center, 27 Nanbinhe Road, Xicheng District, Beijing, China, 100055.

Phone: +86 400-116-9800

Fax: +86 10 63338230

E-mail: sales@can-gas.com

Website: www.can-gas.net